



**STANDARD FINISHES**  
Black, White, & Silver



UP TO 126 lm/W PERFORMANCE				
INDIRECT LIGHT				
DIRECT LIGHT	375 lm/ft	500 lm/ft	750 lm/ft	1000 lm/ft
375 lm/ft	6.00	7.00	9.00	11.25
500 lm/ft	7.25	8.25	10.25	11.50
750 lm/ft	9.75	10.50	12.75	13.75
1000 lm/ft	12.25	13.00	14.75	16.50
1250 lm/ft	14.75	15.75	17.50	19.25

Performance based on 4-foot luminaire at 4,000K @ 25-degrees C



LIGHT LOSS FACTOR		
CCT	CRI	%
4000K	84+	100%
3500K	84+	97.1%
3000K	84+	95.7%
2700K	84+	94.1%
4000K	92+	88.9%
3500K	92+	85.5%
3000K	92+	83.8%
2700K	92+	82.4%



## ORDER GUIDE

EOS 4.0-W-DI															
A	B	C	D	E	F	G	H	I	J	K	L	M (Multiple Selections)			

EXAMPLE: EOS40-W-DI | ASY | 500 | LAM | 500 | 6 | 45K | 8 | 2 | UNV | S1 | W

## OPTIONS

A. MODEL	B. DIRECT OPTICS	C. DIRECT DISTRIBUTION	D. INDIRECT OPTICS	E. INDIRECT DISTRIBUTION	F. LENGTH	G. COLOR TEMPERATURE
EOS 4.0-W-DI	LAM Lambertian ASY Asymmetric GRZ Graze	375 500 750 1000 1250 XXX	375 lm/ft 500 lm/ft 750 lm/ft 1000 lm/ft 1250 lm/ft Custom lm/ft	LAM Lambertian	375 500 750 1000 XXX	375 lm/ft 500 lm/ft 750 lm/ft 1000 lm/ft Custom lm/ft
					2 2 ft (24 in) 3 3 ft (36 in) 4 4 ft (48 in) 5 5 ft (60 in) 6 6 ft (72 in) 7 7 ft (84 in) 8 8 ft (96 in) XXX System Run PATxH Pattern	27K 2700K 30K 3000K 35K 3500K 40K 4000K WCT White Color Tuning 2700K - 6500K

NOTES

Asymmetric direction is determined by lens position. Field adjustable for wall side or room side throw.	Consult factory for outputs between min and max.	Consult factory for outputs between min and max.	Refer to Pattern configuration guide below for nomenclature. Please see Pattern Guide on p.2 for further details.	WCT - max lm/ft is 1000 based on 80 CRI and 4000K.								
			<table border="1"> <tr> <td>PAT</td> <td>12X24</td> <td>L</td> <td>H</td> </tr> <tr> <td>W</td> <td>X</td> <td>Y</td> <td>Z</td> </tr> </table>	PAT	12X24	L	H	W	X	Y	Z	
PAT	12X24	L	H									
W	X	Y	Z									

H. CRI	I. CIRCUIT	J. VOLTAGE	K. DRIVER
8 9	80+CRI 90+CRI	1 1-Circuit 2 2-Circuit	UNV 120-277v 347 347v
			S1 Osram SensiLUM Daylight/Harvest/Occ Sensor (FD-301) LDE1 Lutron Athena Wireless Node (RF-only) in White ELO Lutron Athena Wireless Node (RF-only) in Black DXL Lutron Athena Wireless Node (RF-only) in Silver

90 CRI option has an R9 value greater than 60.

347 may not be available in all configurations.

AWN-R-W, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.

## OPTIONS

L. FINISH	M. CONTROLS & FACTORY OPTIONS
W White B Black S Silver CC Custom Colors	<ul style="list-style-type: none"> <li>NONE Leave Blank</li> <li>AWN-R-W Lutron Athena Wireless Node (RF-only) in White</li> <li>AWN-R-B Lutron Athena Wireless Node (RF-only) in Black</li> <li>VDO Lutron Vive (RF/Daylight/Occ)</li> <li>VRF Lutron Vive RF Fixture Control</li> <li>SPD Osram SensiLUM Daylight/Harvest/Occ</li> <li>CLM Osram Connecting Light Module (CLM)</li> <li>DAY Wattstopper Daylight Sensor (FD-301)</li> <li>OCC Wattstopper Occ Sensor (FS-205v2)</li> <li>DOC Enlighted Daylight/Harvesting Occ (SU-5E-01)</li> <li>EB Wattstopper Occ Sensor (FS-205v2)</li> <li>EC Enlighted Daylight/Harvesting Occ (SU-5E-01)</li> <li>NL Emergency Battery (10-Watt) Emergency Circuit Night Light Circuit</li> </ul>

Consult factory for custom colors.

AWN-R-W, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.

EB option only available for lengths 4ft or greater.

May choose more than one option in this category.

**LIGHT SOURCE**

Long life name brand LED chips and boards to ensure the highest of quality while providing even and smooth illumination throughout our luminaires.

Our luminaires are available in 2700K, 3000K, 3500K and 4000K color temperature as well as White Color Tuning (2700-6500K).

Optional 80CRI or 90CRI available in all CCT options.

**LUMEN MAINTENANCE**

The projected lumen maintenance of the name brand mid-powered LED's are projected to maintain 80% (L80) of their initial output for +80,000 hours.

**CONSTRUCTION**


The housings are constructed of (6063T5) extruded aluminum. Our internal joiner system is designed to the highest of standards to ensure our precision cut housings align and fit tightly without light leak. Our precision fitting end caps are constructed out of die cast aluminum and our steel reflectors are painted white.

**FINISH**

Polyester powder, low gloss textured paint finish applied after a multi-stage pretreatment. Standard luminaire finishes include white, silver, and black. Custom color options are available. (Consult Factory).

**CORNERS**

Precision mitered and seam welded corners are fully illuminated.



**OPTICS**

Snap in extruded frosted acrylic lens

**DRIVERS**

All of our luminaires come standard with 1% dimming and THD <20% utilizing 0-10v constant current protocol. 120v/277v is standard with the option of 347v. Driver ambient operating temperature -30°C to +50°C.

**EMERGENCY**

An integral factory installed 10 watt emergency battery pack. Emergency circuit and Night Light circuit options are available.

**LUMINAIRE WEIGHT**


Our EOS 4.0 Wall Direct/Indirect luminaire series are available in 2', 3', 4', 5', 6', 7' and 8' individual lengths or continuous row configurations. Continuous row configurations are joined together on-site utilizing the joiner kits provided.

**PATTERN GUIDE**


W. PATTERN		X. PATTERN DIMENSIONS		Y. PATTERN CODE		Z. PATTERN ORIENTATION	
Pattern	PAT	Enter length of each segment in pattern separated by an "x"	AxB	L Pattern	L	Horizontal	H

**NOTES**

Dimensions for Patterns are based on outside dimensions of the pattern.  
 Patterns in all cases will require a signed-off submittal prior to release of an order.  
 For Patterns created against walls, the layout will be created using inside wall dimensions from drawings received.



Above code gets entered in "D" LENGTH field of ordering guide.



CONTINUOUS RUN ORDER GUIDES

Please use the following run guides for fixture ordering. If your product will require a submittal, our in-house Application Engineering Team will work closely with you on your project.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
9	6' + 3'
10	6' + 4'
11	6' + 5'
12	6' + 6'
13	6' + 7'
14	8' + 6'
15	8' + 7'
16	8' + 8'
17	6' + 5' + 6'
18	6' + 6' + 6'
19	6' + 7' + 6'
20	8' + 4' + 8'
21	8' + 5' + 8'
22	8' + 6' + 8'
23	8' + 7' + 8'
24	8' + 8' + 8'
25	5' + 8' + 8' + 4'
26	4' + 6' + 6' + 6' + 4'
27	6' + 8' + 8' + 5'
28	6' + 8' + 8' + 6'
29	7' + 8' + 8' + 6'

\*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
30	6' + 6' + 6' + 6' + 6'
31	6' + 6' + 7' + 6' + 6'
32	8' + 8' + 8' + 8'
33	5' + 8' + 8' + 8' + 4'
34	6' + 8' + 8' + 8' + 4'
35	6' + 8' + 8' + 8' + 5'
36	6' + 8' + 8' + 8' + 6'
37	8' + 8' + 5' + 8' + 8'
38	8' + 8' + 6' + 8' + 8'
39	8' + 8' + 7' + 8' + 8'
40	8' + 8' + 8' + 8' + 8'
41	5' + 8' + 8' + 8' + 8' + 4'
42	6' + 8' + 8' + 8' + 8' + 4'
43	6' + 8' + 8' + 8' + 8' + 5'
44	6' + 8' + 8' + 8' + 8' + 6'
45	7' + 8' + 8' + 8' + 8' + 6'
46	3' + 8' + 8' + 8' + 8' + 8' + 3'
47	4' + 8' + 8' + 8' + 8' + 8' + 3'
48	8' + 8' + 8' + 8' + 8' + 8'
49	5' + 8' + 8' + 8' + 8' + 8' + 4'
50	6' + 8' + 8' + 8' + 8' + 8' + 4'

\*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

